

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 18 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Mensch, 1924 (DCSO records, Vol. 14 Pg. 5930)

A Point 2.61 chs. E. of Hathorn's ¼ sec. cor. of secs. 13 and 18, on E. bdy. of T28S R8W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor. of sec. 18 only, T28S R7½W, with brass cap mkd:
¼S18 |
R7½ |
1924

from which

A Fir 18" dia., bears S.68°W., 51 lks. dist., mkd. ¼ S18 R7½ BT.

A Cedar 40" dia., bears N.56°W., 40 lks. dist., mkd. ¼ S18 R7½ BT.

(A C.S. File 52/79-8 report made a correction of Cedar BT, to N.49°W., 30 lks.)

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/13/1998 - C.S. File 66/2- 31

Found - 2½" dia., brass cap on a 1" O.D. iron pipe protrudes 10" above ground, properly marked. 1924
40" now 44" dia., 12' high Cedar snag with a healed blaze, bears N.49°W., 19.8'. Agrees with C.S. 52/79 1924

18" now badly rotted remains of a D.Fir, no scribing visible, bears S.68°W., 33.7'. Agrees w/rec. 1924

15" dia., G.Fir with a fully healed single blaze, bears S.46°W., 10.5'. (Note this BT not of record, has tag dated 1972. No bearing or dist. on tag)

New BTs- 9" dia., G.Fir, double blazed & scribed "¼ S18 CS BT" bears N.26½°W., 15.0'

13" dia., Maple, double blazed & scribed "X CS BT" bears S.67°E., 20.0'. Note BT not in section.

Corner lies approx. 100' east of end of road.