

TOWNSHIP 28 RANGE 07½ POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec Cor for 7 & 18 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Mensch, 1924 (DCSO records, Vol. 14 Page 5937)

Intersect the W. bdy. of T28S R7W, 13.67 chs., S.0°54'E. from
the cor. of secs. 7 and 18. At the point of intersection
Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the
ground, with brass cap mkd: T28S:

 S7:
 S18:
 R7½W:
 1924

from which

 A B.Oak 12" dia., bears S.68°W., 54 lks. dist., mkd.

 T28S R7½W S18 BT.

 A Fir 20" dia., bears N.13°W., 18 lks. dist., mkd.

 T28S R7½W S7 BT.

Doug. County Surveyors Office - James Byron, Deputy - Milo
Godfrey; Clete Putnam - May 1961 - C.S. File 52/79-5

Found - Brass cap at corner. The SW BT is now snag, shows
good scribing. The NW BT is alive, shows good
scars.

New BT - 20" R.Fir bears S.48°W., 32.1 ft. scribed S18 T28S
R7½W CS BT.