

TOWNSHIP 28 RANGE 07½ POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 7 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Mensch, 1924 (DCSO records, Vol. 14, Pg 5928)

Set an iron post, 3 ft. long, 1" dia. 28" in the ground, for
¼ sec. cor. of sec. 7 only, T.28 S., R.7½ W., with brass cap
marked:

¼ S7 |
R 7½ |
1924

from which:

A Fir, 12" dia. bears S.41°W., 19 lks. dist. mkd. ¼ S7
R7½ BT.

A Fir, 16" dia. bears N.5°W., 28 lks dist. mkd. ¼ S7 R7½
BT.

Douglas Co. Surveyors Office - Randall Smith, Stephen Flause;
May 23, 1994 - C.S. File 64/51-23

Found - 2½" Brass cap on a 1" O.D. iron pipe protruding 8"
above ground. (1924)

Accessories Found -

16" now 22" dia. D.Fir with a fully healed single blaze,
bears N.5°W., 17.6 ft. (rec. N.5°W., 18.5 ft.) orig BT.

12" now 17" dia. D.Fir with a fully healed single blaze,
bears S.41°W., 12.5 ft. orig. BT.

New Accessories -

12" dia. Madrone, double blazed and scribed "¼ S7 CS BT"
bears N.34°W., 32.2 ft.

4" dia. Gnarly Butt I.Cedar, double blazed and scribed "X
BT" root crown bears S.63°W., 17.6 ft.