

TOWNSHIP 28 RANGE 07½ POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. for 6 & 7 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Mensch, 1924 (DCSO records, Vol. 14 Pages 5937-38)

Intersect the W. bdy. of T28S R7W, 11.04 chs. S.2°03'W. from the cor. of secs. 6 and 7. At the point of intersection Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd: T28S:

S6:
S7:
R7½W:
1924

from which

A Laurel 20" dia. bears S.53°W., 20 lks. dist. mkd. T28S R7½W S7 BT.

A Fir 12" dia., bears N.31°W., 43 lks. dist., mkd. T28S R7½W S6 BT.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - May 1961 - C.S. File 52/79-12

Found - Brass cap at corner and SW BT OK.
New BT - 12" Cedar bears N.22°E., 4.3 ft. scribed ¼ S CSBT.

Doug. County Surveyors Office - Larry Monrean, Deputy - P.L. Earle; K. Cheney - Dec. 6, 1976 - C.S. File 59/26-19

Found - 1924 GLO brass cap, properly mkd., and firmly set. 20" Laurel, now broken & laying on ground. Stump bears S.53°W., 14.6 ft. (Rec. 13.2 ft.)
12" Fir, now broken & laying on ground. Stump bears N.31°W., 29.2 ft. (Rec. 28.4 ft.)
12" now 14" Cedar bears N.28°E., (Rec. N.22°E.) 4.3 ft. Tree blazed, partially healed, some scribing visible.

New BTs -10" Cedar bears S.23°W., 65.3 ft. Tree double blazed and scribed "T28S R7½W S7 CS BT".

13" D.Fir bears N.28½°W., 52.8 ft. Tree double blazed and scribed "T28S R7½W, S6 CS BT"

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 19993-4)