

TOWNSHIP 28 RANGE 07½ POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 6 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Mensch, 1924 - (DCSO records, Vol. 14 Pages 5925-26)

At a point, 5.28 chs. East of Hathorn's 1/4 sec. cor. of secs. 1 & 6 on the E. bdy. of T28S R8W -
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor. of sec. 6 only, T.28S., R7½W., with brass cap mkd:
 ¼ S6 |
 R7½W |
 1924

from which
 A Willow 6" dia., bears S.55°W., 7 lks. dist. mkd. ¼ S6 R7½ BT.
 A Fir 16" dia., bears N.47°W., 35 lks. dist. mkd. ¼ S6 R7½ BT.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam - May 1961 - C.S. File 52/79-12

Found - 1924 Brass cap at corner.
 16" now 22" Fir stump N.47°W., 23.1 ft. We open and find good scribing
 SW BT not found.
New BTs -12" R.Fir bears N.75°W., 28.7 ft. scribed ¼ S6 CSBT.
 14" R.Fir bears N.29½°W., 39.7 ft. scribed ¼ S6 CSBT