

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 040010

PRIMARY CORNER DESCRIPTION NE Cor. Huntley DLC #40

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original DLC survey by Bowman and Burnett under Contract date
Sept. 24, 1855

Set a post as per instructions, from which
A W.Oak 34" dia., bears S.76½°W., 203 lks.

Doug. County Surveyors Office - James Byron, Deputy - Milo
Godfrey; Clete Putnam - Aug. 8, 1962 - C.S. File 49/50-60

Found - Orig. 34" now 50" W.Oak S.76½°W., 134.0 ft.,
previously opened, shows good scribing C 40 BT.
By ring count and growth of tree, this BT was
rescribed. I believe original face is still
covered.

Also find 6" x 10" x 30" sandstone at corner.
Set Brass cap alongside cor. stone & mkd:
County Surveyor's Office, 1962

DLC 40 | T28S R7W
NE |

New BT - 14" W.Oak bears N.16°W., 140.3 ft. scribed CL 40 CS
BT.

Rescribed 50" W.Oak, S.76½°W., 135.3 ft. mkd. NE CL 40 CS BT.

Found Brass cap, Eugene Bloom, March 1985, M 98-32
Fd. Ok by D.Bentz, 10/96, 1996-0107 A&B

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J.
Flause - 5/11/1998 - C.S. File 66/2-23

Found - 2½" dia., brass cap on a 1½" O.D. iron pipe,
protrudes 10" above ground, properly marked. 1962
Sand stone top measures 10"x6" protrudes 8" above
ground, no marks vis. (Source unknown)

Stone is along West edge of BC/IP

34" now rotted remains of an Oak found near record
"S.76½°W., 135.3 ft." OBT

14" now 23" dia., W.Oak with a fully healed double
blaze, bears N.16°W., 140.3', agrees w/rec. 1962

New B0s- Bearings & Dist. taken from BC/IP

West end of concrete weir bears S.13½°E., 51.7'.

7" dia., W.Oak, double blazed & scribed "NE DLC 40
CS BT" bears N.81°W., 95.5'.

DCS0 drill cap stamped "CHING 1985" bears S.41½°W.,
156.6'. BC is in SW cor. of concrete box culvert.

Corner lies at the intersection of a three way fence corner.
See sketch in file.

Fd. Ok 1/2024 - B Heichel - 2024-0007 _____