

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 047020

PRIMARY CORNER DESCRIPTION NW Cor. Huntley DLC #47

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original DLC survey by Bowman and Burnett under Contract date  
Sept. 24, 1855

-----  
Set a post on sec. line marked as per instructions, from  
which  
A B.Oak 24" dia., bears S.40°E., 17 lks.

Bureau of Land Management resurvey by James E. Jelley, under  
Group #878 - Survey July/Aug. 1975 (DCSO records, Vol. 37  
Pages 15418-19)

-----  
Point for cor. at proportionate distance; there is no  
remaining evidenc of the original corner.  
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the  
ground, with brass cap mkd:     T 28 S R 7 W  
  S 10  
  S 15 | C 47  
  1975

from which  
A Fir 15" dia., bears S.28½°E., 22 lks. dist.,  
mkd. C 47 BT.  
A Fir 9" dia., bears S.65°W., 30½ lks. dist., mkd.  
T28S R7W S15 BT.  
A Fir 14" dia., bears N.76 3/4°W., 7 lks. dist., mkd.  
T28S R7W S10 BT.

Fd 1975 BC BY 5/2018 by M HeimburgerM174-41