

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 047050

PRIMARY CORNER DESCRIPTION SSW Cor Huntley DLC #47

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original DLC survey by Bowman and Burnett under Contract date
Sept. 24, 1855

Set a post as per instructions, from which
A Dogwood 5" dia., bears N.30°E., 47 lks.

F.C. Frear, Deputy Co. Surveyor - For: Lloyd Swan & Gus
Pankey June 13, 1917 - Vol. 3 Pg. 15; Field Book 44 Pg 16

I make diligent search here for old evidence and find a dog-
wood stump that agrees very well with two original field
notes, also other surveyor signs are in evidence and I RESET
this cor. as recorded from this due west line, and note that
said corner is 0.96 chs. South of the sec. line between secs.
15 and 22.
Stump of Dogwood bears N.25°E., 42 lks.
I set a 6" x 8" x 12" creek boulder for the cor. from which
A 36" Fir bears N.10°W., 119 lks., I mark it C.S.C.C. 47

Bureau of Land Management survey by James E. Jelley under
Group #878. Survey July/Aug. 1975 (DCSO records, Vol. 37 Page
15421)

The Exterior cor. on the S. bdy. of DLC #47, perpetuated and
recorded by F.C. Frear, 1917, from orig. evidence no longer
in existence, monumented with an I.P. 2" dia., firmly set,
projecting 4" above ground.

At the corner point
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the
ground, with brass cap mkd: T 28 S
 R 7 W C 47
 S 22 _____
 1975

from which
A Fir 10" dia., bears N.66½°E., 36½ lks. dist. mkd C47 BT.
A Fir 12" dia., bears N.50°W., 42 lks. dist., mkd. T28S R7W
S22 BT.
Reset iron pipe alongside iron post.