

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 049020

PRIMARY CORNER DESCRIPTION NW Cor. Freeman DLC #49

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original DLC survey by Bowman and Burnett under Contract date Sept. 24, 1855

-----  
Set a post as per instructions, from which  
A Laurel 20" dia., bears S.60°E., 30 lks.

-----  
G.G. Stewart, Deputy - Wit: C. Crocker; V. Johnson - Oct. 1922 - Vol. 3 Pg. 125; C.S. 5/25; M 5-70

-----  
Set Iron pipe, from O.B.T., badly rotted. Corner checks with orig. line blazes. Marked  
B.Oak 16" dia., bears N.86°E., 9.8 ft.  
B.Oak 18" dia., bears N.8½°W., 18.5 ft.

-----  
Doug. County Surveyors Office - V.R. Tracy, Deputy - Jack Heritage; V. Perron - Sept. 1968 - C.S. File 52/79-33

-----  
Found - 1/2" I.P. 18" long & orig. BTs recorded by Stewart. 16" now 18" B.Oak 14 ft. high snag, N.86°E., 9.8 ft. scribe marks visible on opened blaze.  
18" B.Oak, now only stub of stump & burned log remains, N.8½°W., 18.5 ft., no scribe found.  
Set Brass cap at cor. mkd: County Surveyors T 28 S R 7 W  
Office, 1968 N.W. D.L.C. | 49  
Reset I.P. alongside.  
New BTs -6" D.Fir N.29°E., 32.8 ft. mkd. "N.W. DLC 49 CS BT."  
6" D.Fir S.13°W., 41.4 ft. mkd. "N.W. DLC 49 CS BT."  
This corner lies on steep south slope densely covered with Laurel and few Fir.

-----  
Fd. OK - B. Shaner - June 30, 1997 - C.S. 65/15-3C & M 124-56  
Found OK by D. Edwards, Jan. 2001 - C.S. File 65/34-2  
Fd. Ok - K. DeGroot - Feb. 2006 - 2006-0029  
FD. BC by D. Edwards, 7/7/2008 - C.S. File 65/64-5