

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 049030

PRIMARY CORNER DESCRIPTION WC WSW Cor. Freeman DLC #49

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original DLC survey by Bowman and Burnett under Contract date Sept. 24, 1855</p> <p>-----</p> <p>Set a post as per instructions, from which A Laurel 20" dia. bears S.60°E., 30 lks.</p>
<p>G.G. Stewart, Deputy - Witnesses: C. Crocker; V. Johnson Oct. 1922 - Vol. 3 Page 125; C.S. 5/25; M 5-70</p> <p>-----</p> <p>Set pointed rock for corner from O.B.T. Marked Fir 12" dia., bears N.75½°E., 33.0 ft. Fir 12" dia., bears N.32°E., 64.5 ft.</p>
<p>Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; S.A. Bilow - Nov./Dec. 1958 - C.S. File 49/50-17</p> <p>-----</p> <p>Found - Both BTs as recorded by Stewart &amp; each is now 16" stump, good scribing visible. Pointed rock at corner. Set Brass cap alongside corner rock marked: "SW Ext. L DLC 49, T28S R7W County Surveyor's Office, 1958". New BTs -14" R.Fir bears N.7°E., 5.2 ft. scribed SW CL 49 CS BT. 13" Pine bears S.44°E., 9.3 ft. scribed SW CL 49 CS BT.</p>
<p>Doug. County Surveyors Office - Vernon R. Tracy, Deputy - Jack Heritage; V. Peron - Sept. 1968 - C.S. File 52/79-35</p> <p>-----</p> <p>Found - 1958 DCS0 brass cap &amp; BTs as recorded by Stewart and Byron. BTs all sawed stumps, except 14" Pine S.44°E., 9.3 ft. alive, scribe visible on unhealed blaze. New BT - 7" W.Oak N.81°E., 9.1 ft. mkd. "S.W. Ext. L DLC 49 CS BT" This corner lies about 400 ft. N.45°E., of junction of Hwy 42 and Olalla Road on S. side Hwy 42 in R/W clearing area.</p>
<p>Found Brass cap, March 1992, H. Northcraft, M 115-16</p>
<p>Douglas County Surveyors Office - Randall Smith &amp; Stephen Flause - July 9, 1996 - C.S. 64/69-9</p> <p>-----</p> <p>Mon. Fd.- 2½" Brass cap on a 1½" O.D. iron pipe protruding 15" above ground. (1958 DCS0) Corner stone portion above ground measures 4"x3"x2" above ground. Stone is along southerly edge of BC/IP (1922 Stewart).</p> <p>(Cont. Next Page)</p>

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 049030

PRIMARY CORNER DESCRIPTION WC WSW Cor. Freeman DLC #49

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Bt's Fd.- 16" dia. 3' high rotted D.Fir stump, with illegible scribing visible on a previously opened blaze, bears N.72½°E., 33.5'.  
16" dia. 3½' high rotted D.Fir stump, with scribing visible "CL 49 BT" on a previously opened blaze, bears N.32°E., 64.5'.  
14" dia. 2' high rotted D.Fir stump, with scribing visible "BT" on a previously opened blaze, bears N.7°E., 5.2'.  
23" dia. I.Cedar, with a fully healed double blaze and attached BT tag, bears S.44°E., 9.3' Note: species of BT wrong in 1958.  
8" dia. W.Oak, with a fully healed single blaze, bears N.81°E., 9.1'.  
NOTE: The above BT's will be gone, cleared by new road construction.  
New 5/8" Iron rod (S.H.R.W.) we tie to corner, bears S.16½°E., 60.93'.  
Mon. Set- BC/IP and stone are removed and reset at a reference position. BC/IP measures 36" long, stone measures 5"x8"x12". The stamping "1996 S.89°W. 150 FT" are added to BC.  
BC/IP protrudes 9" above ground stone is set along northerly edge of BC/IP protrudes 4" above ground.  
BC/IP is set N.89°E., 150' from corner  
New Accessories - are to reference point (BC/IP)  
5/8" I.R. (S.H.R.W.) bears S.65¼°W., 145.86'.  
9" dia. Maple, double blazed and scribed "RP WSW DLC 49 CS BT" bears N.15½°E., 35'.  
Double trunked Maple, double blazed and scribed "RP WSW DLC 49 CS BT" on 8" dia. easterly trunk, bears N.75½°W., 32.4' to center bask of easterly trunk.  
6" dia., D.Fir double blazed and scribed "RP WSW DLC 49 CS BT", bears N.67½°E., 11'.  
Area around corner is to be cleared for new road construction. BC/IP and stone are now reference points to original corner position.

Fd. OK - B. Shaner - Jun. 30, 1997 - C.S. 65/15-3B & M 124-56  
Fd. Ok - K. DeGroot - Feb. 2006 - 2006-0029  
FD BC, SHRW IR, & 3 BTs by C Sweeden, 12/2015 - M170-34