

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 050010

PRIMARY CORNER DESCRIPTION NE Cor. Thomas Croxton DLC #50

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original DLC survey by Bowman and Burnett under Contract date Sept. 24, 1855 (DCSO DLC records Pg 504)

-----  
Set a post as per instructions, from which  
A W.Oak 18" dia., bears S.35°W., 433 lks.

BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20026-7)

-----  
Point for the NE. cor. of DLC No. 50, at proportionate position, determined by the Compass Rule method; there is no remaining evidence of the original corner.

Set a "PK" nail in the asphalt-surface of State Highway 42. from which

An ash, 22" diam., bears S.6½°E., 290 lks., mkd. X BT.

A stainless steel post, 28" long, 2½" diam., set 22" in the ground, for a reference monument, bears S.64°E., 233.2 lks., with brass cap mkd. RM C50 154 FT TO COR 1993 and an arrow pointing to the corner.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

The reference monument is located in a woven wire fence extending N.65°E. and S.65°W.

The NE. abutment of a concrete bridge spanning Lookingglass Creek, bears S.70 3/4°W., 6.28 chs.