TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 050020

PRIMARY CORNER DESCRIPTION NW Cor. Thomas Croxton DLC # 50

Alias Description
Alias Description
Alias Description
Alias Description

Original DLC survey by Bowman and Burnett under Contract date Sept. 24, 1855 (DCSO DLC records Pg 503)

Set a post as per instructions Quadrangular trench with stone in center.

BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20027-8)

Point for the NW. cor. of DLC No. 50, at proportionate position, determined by the Compass Rule method; there is no remaining evidence of the original corner.
Set a stainless steel post, 28" long, 2½" diam., 32" in the ground, with brass cap mkd. T28S R7W

C55 | S28/C50

1993

from which
A pine, 17" diam., bears S.72½°E., 359 lks., mkd. X BT.
A pine, 17" diam., bears S.9½°E., 287 lks., mkd. C50 BT.
Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
The corner is located in an open field.

Fd. BC by G. Lang, 7/2010 - 2010-0030
Fd BC by D Feigel, 5/2020 - 2020-0037