

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 050030

PRIMARY CORNER DESCRIPTION SW Cor. Croxton DLC #50

Alias 053040 Description Ext. NW Cor. Olmstead DLC #53
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original DLC survey by Bowman and Burnett under Contract date
Sept. 24, 1855 (DCSO DLC records Pg 503)

Set post, from which
A B.Oak 6" dia., bears N.85°E., 38 lks.

Herbert Northcraft, For: Cyril Phillips et al. Feb. 1972 -
M 44-41

Found - 1¼" I.Pipe, damaged. (*I could find no record source
that "set" this I.P. v.l. 4/93*)
18" Fir snag, N.26°E., 6.5 ft. scribed CL #50 1584
for SW Cor. DLC #50, T28/7
Owners Meutzel and Dysert agreed.
Reset - 5/8" x 30" Iron Rod.

Fd. Ok by Mark Heimbürger, Aug. 1995 - 1995-0095 A&B

BLM dependent resurvey by Bryan S. Seibold, & Robert J.
Chappel, Cadastral Surveyor, under Group #1585, surveyed May
1991/May 1994 - (DCSO records Vol. 52 Page(s) 20028)

The SW. cor. of DLC No. 50, identical with the most westerly
NW. cor. of DLC No. 53, and on the E. bdy. of DLC No. 51,
perpetuated by Boyer, further perpetuated by Northcraft, in
1972,; monumented with an iron rod, 5/8" diam., firmly set
flush with the ground, from which the remains of a bearing
tree mkd. by Boyer:

A fir snag, 18" diam., bears N.23½°E., 9½ lks., with
scribe marks C 158 visible on open decaying blaze.
Set a stainless steel post, 28" long, 2½" diam., 23" in the
ground, directly over the iron rod, with brass cap mkd.

T28S R7W
C50
C51 _____
C53
1993

from which new bearing trees

A fir, 17" diam., bears N.42°E., 41 lks., mkd. C50 BT.
A maple, 13" diam., bears S.26½°E., 49 lks., mkd. C53 BT.
Deposit a white "DEEP-1" magnetic marker at base of stainless
steel post.

The corner is located at a fence corner with woven wire
fences extending N., S., and E.

Fd. OK by G. Lang, Dec. 1999 - LP 2000-0019