

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 050060

PRIMARY CORNER DESCRIPTION SE Cor. Thomas Croxton DLC #50

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original DLC survey by Bowman and Burnett under Contract date  
Sept. 24, 1855 (DCSO DLC records Pg 504)

-----  
Set a post as per instructions, from which  
A B.Oak 8" dia., N.50°W., 61 lks.

BLM dependent resurvey by Bryan S. Seibold, & Robert J.  
Chappel, Cadastral Surveyor, under Group #1585, surveyed May  
1991/May 1994 - (DCSO records Vol. 52 Page(s) 20026)

-----  
Point for the SE. cor. of DLC No. 50, at proportionate  
position, determined by the Compass Rule method; there is no  
remaining evidence of the original corner.  
Set a stainless steel post, 28" long, 2½" diam., 23" in the  
ground, with brass cap mkd. T28S R7W  
C50 S27  
1993

from which  
A maple, 9" diam., bears N.75°W., 64 lks., mkd. C50 BT.  
The most southerly trunk of a triple trunk madrone, 10"  
diam., bears N.30 3/4°W., 17 lks., mkd. C50 BT.  
Deposit a white "DEEP-1" magnetic marker at base of stainless  
steel post.