

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 053010

PRIMARY CORNER DESCRIPTION NE Cor. John Olmstead DLC #53

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original DLC survey by Bowman and Burnett under Contract date Sept. 24, 1855 (DCSO DLC records Pg 507)

Set a post as per instructions, from which
A W.Oak 15" dia., bears S.18°W., 262 lks.
House bears S.80°W., 25 chs.

BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20029)

From the point for the NE. cor. of DLC No. 53, on the S. bdy. of DLC No. 50, determined by the compass rule method; there is no remaining evidence of the original corner.
Set a stainless steel post, 28" long, 2½" diam., 27" in the ground, with brass cap mkd. T28S R7W

C50

C53 | S27
1993

from which
A pine, 8" diam., bears S.0 3/4°W., 78 lks., mkd. C53 BT.
An oak, 12" diam., bears S.30 3/4°W., 105 lks. mkd C53 BT.
Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
The corner is located South, 0.25 chs. dist. of a dirt road, 15 lks. wide, bears E. and W.

Fd. BC & BTs by N Hibbs, 4/2017 - M171-26A&B