

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 053080

PRIMARY CORNER DESCRIPTION SE Cor. John Olmstead DLC #53

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original DLC survey by Bowman and Burnett under Contract date Sept. 24, 1855 (DCSO DLC records Pg 507)

Set a post as per instructions, from which
A W.Oak 4" dia., bears N.25°W., 18 lks.

BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20029-30)

Point for the SE. cor. of DLC No. 53, at proportionate position, determined by the Compass Rule method; there is no remaining evidence of the original corner.
Set a stainless steel post, 28" long, 2½" diam., 26" in the ground, with brass cap mkd. T28S R7W
C53 | S34

1993

from which
An oak, 22" diam., bears N. 80½° W., 44 lks. dist., mkd. C53 BT.

A madrone, 7" diam., bears N. 49 3/4° W., 16 lks. dist., mkd. C53 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

The corner is located N. 84° W., 1.90 chs. dist. of a fence corner, with woven wire fences extending N. 75° E., S. 75° W., and S. 10° E.

Fd. BC & BTs by N Hibbs, 4/2017 - M171-26A&B