

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 054050

PRIMARY CORNER DESCRIPTION SW Cor. Hull DLC #54

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original DLC survey by Bowman and Burnett under Contract date
Sept. 24, 1855

Set post, from which
 A W.Oak 12" dia., bears N.30°E., 81 lks.

G.G. Stewart, Deputy - Wit: C. Crocker; J.H. Porter - Sept.
1922 - For: Bogard Real Estate - Vol. 3 Pg. 126; C.S. Files
3/40 and 5/22

Found O.B.T. standing. Set I.Pipe for corner & marked:
 B.Oak 18" dia., bears N.54½°E., 136.9 ft.
 W.Oak 20" dia., bears N.20°W., 107.5 ft.

Doug. County Surveyors Office - James Byron, Deputy - April
1957 - C.S. File 47/176; RM 1-15

Found - 1/2" Pipe at corner.
 24" B.Oak N.51½°E., 136.9 ft., has been chopped open
 and old face rotted.
 No trace of tree to NW.
 A 36" W.Oak, N.30°E., 54.0 ft. shows definite axe
 scar facing corner pipe. Reblaze and scribe this
 tree "SW Cl 54 CS BT".
Blaze and Scribe:
 6" W.Oak S.82°E., 37.9 ft. scribed "SW Cl. 54 CSBT".

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 5/25/94 - C.S. File 64/51-19

Found - ½" I.D. iron pipe, 2" below ground. (1922)
 12" now 42" dia., W.Oak with a fully healed double
 blaze bears, N. 30°E., 54.0' (agrees w/rec) OBT
 18" now 20" dia., 2' high rotted oak stump with a
 possible low blaze, bears N.51½°E., 136.9'
 (agrees w/rec) 1922
 6" now 20" dia., W.Oak with a fully healed double
 blaze bears, S.82°E., 37.9' (agrees w/rec) 1957
Set - 2 3/8" dia., Brass Cap on a 1 3/8" O.D. by 32" long
 Iron Pipe is set at FD position of ½" I.P. BC/IP
 protrudes 6" above. ½" I.P. measures 21" long is
 set along north edge of BC/IP flush with ground.
 Stamped: DOUGLAS COUNTY SURVEYOR'S
 T 28 S
 DLC R
 | 54 7
 SW COR W
 OFFICE
 1994

(Cont. Next Page)

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 054050

PRIMARY CORNER DESCRIPTION SW Cor. Hull DLC #54

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 11" dia., W.Oak, double blazed and scribed "SW DLC 54 CS BT" bears, S.64½°W., 21.8'.

5" dia., W.Oak, double blazed and scribed "SW DLC 54 CS BT" bears, N.67°E., 15.4'.

3/4" I.R. bears S.41½°E., 40.7'.

Note - Corner lies at the intersection of an Easterly-Westerly and Northerly running fence lines.
See sketch in C.S. File.

Fd Ok by K. DeGroot, July 2004 - M145-29

FD. BC by R. Quimby, 10/2008 - 2009-0027A

Fd ok by G. Lang. 12/2010 - M161-58