

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 055050

PRIMARY CORNER DESCRIPTION SW Cor. Saar DLC #55

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original DLC survey by Bowman and Burnett under Contract date Sept. 24, 1855

Set a post as per instructions, from which
A Pine 50" dia., bears N.30°E., 156 lks.

G.G. Stewart, Deputy - For: Bogard Real Estate, Sept. 1922
Vol. 3 Pg. 126; C.S. Files 3/40 and 5/22

W.Oak 8" dia., bears N.49°W., 65.2 ft.
Pine 6" dia., bears S.38°W., 122.5 ft.
Drove Iron pipe. Corner set as per gov't field notes from NW corner of DLC Cl. 55.

I.P. found OK, July 1981, George Grubb, M 88-34
Found OK by N. Hibbs, Nov. 2000 - M132-72

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 2/8/2001 - C.S. File 66/19-34

Found - ½" I.D. iron pipe, protrudes 3" above ground. 1922
8" now 32" dia., W.Oak fully healed blaze bears
N.49°W., 65.2 ft. 1922
6" now 26" dia., P.Pine showing a fully healed
single blaze bears S.41°W., 122.5 ft. (rec.
S.38°W., 122.5 ft.)
See survey(s) that have ties to close property
corners in area, measurements not checked.
Note - This corner set in 1922 at rec. brg. & dist. from NW
cor. of DLC 55.
Intersection of Tenmile Rd. (Co. Rd. #109) & Sibold
Canyon Rd. is approx. South 100 ft. IP 1 ft. East
of a N-S fence line & 15' West of centerline of
Sibold Canyon Rd.
Compass decl. 17 ¾°E.

fd. 1/2" IP by G. Lang, 7/2010 - 2010-0030