

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 056010

PRIMARY CORNER DESCRIPTION WC NNE Cor McCullough DLC #56

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original DLC survey by Bowman and Burnett under Contract date Sept. 24, 1855

Set a post as per instructions, from which
An Ash 14" dia., bears S.60°W., 36 lks.

G.G. Stewart, Deputy - For: I.B. Nichols, et al Nov. 8, 1922
Vol. 3 Pg. 129; C.S. File 5/28; M 3-74

Set stake in creek from old Pine line tree. Marked:
Fir 18" dia., bears S.54°W., 68.5 ft.
The SW side of South pier of Hwy. bridge over Lookingglass
Creek, N.43°E., 196.8 ft.

GL0 survey by Mensch, 1924 (DCS0 records, Vol. 14 Page 5900)

NE cor. of Cl. #56, which is now in the bed of Ten Mile
Creek. No trace can now be found of the orig. cor., its
position however, has been determined by the County
Surveyor; from which point:
A Fir 22" dia., bears S.54°W., 103 lks. mkd. D.L.C. 56 CS
BT.
Face of South bridge pier bears N.43°E., 298 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo
Godfrey; Clete Putnam - Oct. 12, 1959 - C.S. File 49/50-26

Found - 18" now 36" Fir S.54°W., 68.5 ft. previously opened,
shows good scribing "DLC 56".
Bridge over Creek rebuilt. I do not check tie to pier.
Corner in Creek. I set WIT. COR. 50 ft. West of true corner:
Set Brass cap mkd. County Surveyors Office, 1959, N.E. Cor.
DLC 56 T28S R7W.
New BTs -20" R.Fir bears S.7°W., 41.3 ft. scribed Wit. NE Cl
56 CS BT.
Rescribe now 36" Fir S.33°W., 12.0 ft. Wit NE Cl 56
CS BT.

Found OK, Donald Bentz, Nov. 1988, M 107-34
Found OK, Dec. 1989, Partition plat 1990-0073

continued next page

Alias	Description

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 1/30/2001 - C.S. File 66/19-21

Found - 1959 DCS0 brass cap wit. corner, protrudes 12" out of ground. Corner surrounded by thick! growth of blackberries.
Wit. cor. on west high bank of Tenmile Creek.
18" now 36" dia., 5½" high rotted D.Fir stump, illegible scribe mark found bears S.7°W., 41.3 ft. (1922 BT)
20" now 30" dia., 3 ft. high D.Fir stump with a fully healed blaze bars S.33°W., 12.0 ft. (1959)

Note - Bearings & distances mix up in 1959 on above BTs. This Wit. cor. 50 ft. West of true corner per 1959 DCS0.

New - 18" dia., G.Fir double blazed & scribed "W.C. NNE DLC 56 CS BT" bears S.13½°W., 23.5 ft.
19" dia., G.Fir double blazed & scribed "WC NNE DLC 56 CS BT" bears S.22°E., 12.6 ft.
18" dia., G.Fir double blazed & scribed "WC NNE DLC 56 CS BT" bears N.71°E., 19.4 ft.
14" dia., Myrtle double blazed & scribed "WC NNE DLC 56 CS BT" bears N.38½°E., 44.4 ft.
Center of concrete bridge over Tenmile Creek approx. N.45°E., 200 ft.
Metal Wit. post & sign set 1 ft north of corner.
See last Pg for pictures.

Fd. BC 6/2017 by R. Quimby M173-33

Douglas Co. Surveyor's Office - Crew: Jeff Lorsung - 7/28/2025 - C.S. File 67/61-3

Found - 2½" DCS0 brass cap (properly mkd) proj 16" reference and reset proj 1"
23"x8 ft. G.Fir stump S.13½°W., 22.8 ft. (rec. 23.5 ft) healed double blaze.
15" Myrtle N.38½°E., 44.6 ft. (rec. 44.4 ft) healed double blaze.
Add 3½" mag nails to BTs right side center.
Metal post and sign 1 ft. North
Add New BT tags.

New - ⅝" iron rod with plastic cap set by IE Eng. Per M173-33 bears S.88°03'02"W., 257.19 ft.
12" Ash N.86°E., 50.3 ft. scribed DLC 56 BT on single low blaze.

Note - Compass decl. 14¼°E.
O CRS COORDINATE SYSTEM COTTAGE GROVE-CANYONVILLE ZONE
~~N 42°57'16.04072" W 123°21'43.9219"~~
43°05'22.56853 N 123°34'14.11346 W
SEE LAST PAGE FOR 2001 PICTURES - continued next page

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 056010

PRIMARY CORNER DESCRIPTION WC NNE Cor McCullough DLC #56

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____



Fd. Ok by Bart Heichel - 8/2025 - M185-41