

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 059030

PRIMARY CORNER DESCRIPTION SSW Cor. Coats DLC #59

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original DLC survey by Bowman and Burnett under Contract date
Sept. 24, 1855

Set a post, from which
A Fir 8" dia., bears N.60°E., 40 lks.
A Fir 12" dia., bears S.55°W., 30 lks.

Jesse W. Cole, Co. Surveyor - Wit: W.H. Coats; Walter Coats;
N.E. Richardson - Feb/March 1923 - Vol. 3 Pgs. 141-147; C.S.
File 5/37; M 1-2

Set a rock 10" x 10" x 12" on Hathorn's township line at
proper distance from NW corner of section 31, no evidence of
witness trees to be found.
(This corner supposedly set by Heydon 20 years ago.)

GLO resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pg. 5898)

SW Cor. DLC #59, which is a sandstone, 12x10x6 ins. above
ground. I designate this cor. "Cor No. 5" and mark AP 5 on
NE face; from which
A W.Oak 6" dia., bears N.38°E., 177 lks. dist. mkd. AP 5
DLC 59 bT.
No other tree available.
Find no trace of the old original corner.