

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. 19 & 30 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5745)

Set a post, cor. of secs. 19, 24, 25 and 30, from which
A B.Oak 10" dia., bears N.33°E., 44 lks.
A B.Oak 12" dia., bears S.83°E., 38 lks.
A B.Oak 14" dia., bears S.48°W., 88 lks.
A W.Oak 24" dia., bears N.75°W., 125 lks.

GL0 resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pages 5932-33)

Intersect the point for cor. of secs. 19, 24, 25 and 30, established by Ford, located by record bearing and distance from the orig. NE bearing tree, blazes plain, marks grown over, and not opened. Could not find the SE, SW, or NW BTs. At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 19 and 30 only, with brass cap mkd:

T 28 S
S 19

S 30
R 7 W
1924

from which

A Fir 12" dia., bears S.61°E., 17 lks. dist. mkd. T28S R7W S 30 BT. (New BT)

Orig. BT, a B.Oak 30" dia., bears N.33°E., 44 lks. dist., re-marked T28S R7W S19 BT.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam - May 1961 - C.S. File 49/50-54

Found - Brass cap set by Mensch in 1924.
12" Fir now 16", S.61°E., 11.2 ft.
Old Oak, N.33°E., 29 ft. is down & badly rotted.
New BT - 27" Fir N.35°E., 5.0 ft. mkd. T28S R7W S19 CS BT.

Doug. County Surveyors Office - Randall Smith; Stephen Flause June 26, 1985 - C.S. File 62/28-9

Found - 1924 GL0 survey disk on an I.P., protruding 5" above ground, & leaning 5" west, properly marked. Monument returned to plumb, firmly set & protruding 8" above ground
10" now tipped out and down badly rotted Oak, no marks found. A depression in ground bears N.33°E., 29 ft. Agrees w/rec. Orig. BT.

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. secs. 19 & 30 only, (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

12" now a 17" dia. D.Fir with a fully healed double blaze bears S.61°E., 11.2 ft. (agrees w/rec)
27" now a 27" dia., 4 ft. high D.Fir stump with a fully healed lower blaze and a partially healed upper blaze with scribing visible "W S19 CS", bears N.35°E., 5.0 ft. (agrees w/rec.)
New BTs -16" D.Fir double blazed & scribed "T28S R7W S30 CSBT" bears S.29 3/4°E., 26.9 ft.
7" Madrone bark scribed "T28S R7W S19 CS BT" bears N.29°E., 29.6 ft.
Corner lies on steep NW slope.