TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 19 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5745)

Set qtr. sec. post, from which
A W.Oak 24" dia., bears N.85°E., 60 lks.
A W.Oak 20" dia., bears N.10°W., 100 lks.

GLO resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pages 5931-32)

Intersect the point for ¼ sec. cor., established by Ford, located by record measurements from the orig. BTs. the blazes are plain, marks grown over and not opened.
At the exact cor. point
Set an iron post, 3 ft. long, 1 ins. diam., 28 ins. in the ground, for 1/4 cor. sec. 19 only with brass cap mkd:

¼S19
1924

from which
A W.Oak 8" dia., bears N.68°E., 85 lks. dist. mkd. ¼ S19 BT.
Orig. BT, a W.Oak 30" dia., bears S.89°E. (Not N.85°E.) 60 lks. dist.
Orig. BT, a W.Oak 30" dia., bears N.10°W., 100 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - May 1961 - C.S. File 49/50-54

Found - Brass cap set by Mensch in 1924.
8" W.Oak now 10" N.68°E., 56.1 ft.
30" W.Oak, orig. S.89°E., 39.6 ft., now dead and badly decayed.
New BT - 9" W.Oak N.87°E., 40.3 ft. mkd. ¼ S19 CS BT.