

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. 18 & 19 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5744)

Set a post, cor. of secs. 13, 18, 19 and 24, from which
A Laurel 6" dia., bears S.65°W., 6 lks. dist.
A Maple 4" dia., bears N.25°W., 13 lks. dist.
A Maple 5" dia., bears N.15°E., 15 lks. dist.
A R.Fir 12" dia., bears S.83°E., 12 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy
Milo Godfrey; Clete Putnam - May 1961 - C.S. File 49/50-55

Found - 1924 Brass cap at corner.
Both BTs by Mensch, now down.
Orig. NE BT now partly rotted snag, shows scribe marks.
New BTs -11" W.Fir bears N.69°E., 47.7 ft. scribed S18 T28S
R7W CS BT.
6" W.Fir bears S.64°E., 5.0 ft. scribed S18 CSBT.