

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 18 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5744)

-----  
Set qtr. sec. post, from which  
A B.Oak 10" dia., bears N.65°E., 37 lks. dist.  
A B.Oak 12" dia., bears N.75°W., 28 lks. dist.

GLO resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pages 5929-30)

-----  
Intersect the point for ¼ sec. cor., established by Ford, located by record measurement from the orig. BTs, upon which the marks are illegible.

At the exact cor. point  
Set an iron post, 3 ft. long, 1 ins. diam., 28 ins. in the ground, for ¼ sec. cor. of sec. 18 only, with brass cap mkd:  
| ¼S18  
1924

from which (new bearing trees)  
A Fir 6" dia., bears N.57°E., 9 lks. dist. mkd. ¼ S18 BT.  
A Fir 4" dia., bears S.8°E., 4 lks. dist. mkd. ¼ S18 BT.  
Orig. BTs  
A B.Oak (dead) bears N.65°E., 37 lks.  
B.Oak bears N.73°W., (Not N.75°W.) 28 lks.

Doug. County Surveyors Office - James Byron, Deputy  
Milo Godfrey; Clete Putnam - May 1961 - C.S. File 52/79-7

-----  
Found - 1924 Brass cap at cor. and NE BT., now down, shows scribe marks  
SE BT not found.  
New BTs -12" R.Fir bears N.46°E., 16.6 ft. scribed ¼ S18 CSBT  
10" Cedar bears S.67°E., 25.0 ft. scribed ¼ S18 CSBT

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20042-3)