

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Pages 5743-44)

- 
- Set a post, cor. of secs. 7, 12, 13 and 18, from which
- A R.Fir 30" dia., bears S.50°E., 32 lks. dist.
  - A R.Fir 18" dia., bears S.25°W., 38 lks. dist.
  - A R.Fir 30" dia., bears N.12°E., 200 lks. dist.
  - A R.Fir 24" dia., bears N.30°W., 150 lks. dist.

GLO resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pages 5928-29)

-----  
Intersect the point for cor. of secs. 7, 12, 12 and 18, established by Ford, located by record bearing and measurement from the orig. SE and SW BTs on which the marks are legible. The NE tree is burnt down and the NW tree is entirely destroyed.

At the exact cor. point  
Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 7 and 18 only, with brass cap mkd:

T28S  
S 7  
S18  
R7W  
1924

- from which
- A Maple 12" dia., bears N.62°E., 66 lks. dist. mkd.  
T28S R7W S7 BT.
  - A Fir 14" dia., bears S.81°E., 54 lks. dist. mkd.  
T28S R7W S18 BT.
  - Orig. SE BT, a Fir 36" dia., bears S.50°E., 32 lks.
  - Orig. SW BT, a Fir 36" dia., bears S.25°W., 38 lks.
  - Orig. NE BT, a Fir 36" dia., bears N.12½°E., 164 lks. dist. (Not N.12°E., 200 lks.)

BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 19994-5)

-----  
Beginning at the cor. of secs. 7 & 18 only, on the W. bdy. of the Tp., monumented with an iron post, 2" diam., firmly set, projecting 10" above ground, with brass cap mkd.

T28S  
S 7  
S 18  
R7W  
1924

continued next page

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which an original bearing tree  
A fir, 46" diam., bears S.25°W., 38 lks., with healed  
blaze.  
and bearing trees mkd. by Mensch  
A maple, 18" diam., bears N.63½°E., 66 lks., with healed  
blaze. (Record, N.62°E.)  
A sawed fir stump, 38" diam., bears S.81°E., 54 lks., with  
no marks visible on rotted stump.  
and a bearing tree mkd. by person(s) unknown  
A fir, 22" diam., bears S.44 3/4°E., 31 lks., with healed  
blaze.