

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5743)

- Set a post cor. of secs. 1, 6, 7 and 12, from which
- A Laurel 12" dia., bears S.30°W., 13 lks. dist.
- A R.Fir 8" dia., bears N.35°W., 16 lks. dist.
- A R.Fir 10" dia., bears S.54°E., 21 lks. dist.
- A B.Oak 6" dia., bears N.35°E., 16 lks. dist.

GLO resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pages 5926-27)

The point for cor. of secs. 1, 6, 7 and 12, established by Ford. The record bearings and distances from the original BTs at this cor. are in error and cannot be made to harmonize to the extent necessary to definitely restore the cor. in its orig. position; therefore, I restore the cor. on the blazed line to the N. and in position indicated for the cor. by the facing of the old blazes on the bearing trees.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 6 and 7 only, with brass cap mkd:

T28S
S 6
S 7
R7W
1924

from which (new bearing trees)

 A Fir 14" dia., bears N.28°E., 22 lks. dist. mkd. T28S R7W S6 BT.

 A Fir 12" dia., bears S.71°E., 16 lks. dist., mkd. T28S R7W S7 BT.

Orig. NE BT, a B.Oak could not be found.

Orig. SE BT, a Fir 20" dia., bears S.30°E., 17 lks. dist. (not S.54°E., 21 lks.)

Orig. SW BT, A Laurel 12" dia., dead, bears S.73°W., 10 lks. (Not S.30°W., 13 lks.) plainly marked.

Orig. NW BT, a Fir 18" dia., bears N.72°W., 12 lks. dist. (Not N.35°W., 16 lks.) marks are plain and overgrowth shows this tree to have been marked about 70 years ago.

On the old SE tree, the blazes are plain, the marks are grown over and were not opened.

Doug. County Surveyors Office - Larry E. Monrean, Deputy - P.L. Earle; K. Cheney - Dec. 6, 1976 - C.S. File 59/26-18

Found - 1924 GLO brass cap, properly mkd. and firmly set. (Cont. Next Page)

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

12" now 16" Fir bears S.71°E., 11.0 ft. (Rec. 10.6 ft.) Tree has well healed blaze.
14" Fir now a windfall, bears N.28°E., 14.5 ft.
An orig. 20" now 26" Fir stump bears S.30°E., 11.2 ft. Stump has old blaze.
An orig. 18" now 28" Fir bears N.72°W., 7.9 ft. Tree has poorly healed blaze.
All other BTs are gone.
New BT - 14" D.Fir bears N.80½°E., 48.3 ft. Tree double blazed and scribed "T28S R7W S6 CS BT".

BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 19998)

The cor. of secs. 6 & 7, monumented with an iron post, 2" diam., firmly set, projecting 8" above ground, with brass cap mkd.

	T28S
	S 6
	S 7
	R7W
	1924

from which the remains of an original bearing tree
A fir snag, 25" diam., bears N.72°W., 12 lks., with healed double blaze.
and the remains of a bearing tree mkd. by Mensch
A roothole, bears N.28°E., 22 lks., with uprooted 15" diam. fir alongside, with healed blaze.
and a bearing tree mkd. by Monrean, in 1976,
A fir, 20" diam., bears N.80½°E., 73 lks., with healed blaze.
and a new bearing tree
A pine, 10" diam., bears S.61½°E., 35 lks., mkd. T28S R7W S7 BT.