

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 6 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5743) ----- Set qtr. sec. post, from which     A R.Fir 15" dia., bears S.45°W., 60 lks. dist.     A Willow 4" dia., bears N.40°E., 72 lks. dist.</p>
<p>GLO resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pg. 5925) ----- Point for ¼ sec. cor. located by Hathorn's record tie for the Hathorn ¼ sec. cor. of secs. 1 and 6. At the exact cor. point Set an iron post, 3 ft. long, 1 ins. diam., 28 ins. in the ground, for ¼ sec. cor. of sec. 6 only, with brass cap mkd:                               ¼ S6                             1924 from which     A Fir 18" dia., bears N.23°E., 46 lks. dist. mkd. ¼ S6 BT.     A Fir 14" dia., bears S.36°E., 37 lks. dist. mkd. ¼ S6 BT.</p>
<p>Doug. County Surveyors Office - James W. Byron, Deputy Milo Godfrey; Clete Putnam - May 1961 - C.S. File 52/79-13 ----- Found - 1924 Brass cap at corner.         Both BTs now down. We open SE BT and find good scribing. New BTs - 20" R.Fir bears N.10°E., 34.4 ft. scribed ¼ S6 CSBT           12" R.Fir bears S.71°E., 28.7 ft. scribed ¼ S6 CSBT</p>
<p>Found OK, H. Stockhoff, May, 1981 - M 87-69</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/13/1998 - C.S. File 66/2-29 ----- Found - 2½" dia., brass cap on a 1" O.D. iron pipe, protrudes 12" above ground, properly marked.         18" D.Fir, now root hole near record "N.23°E., 30.4 ft". 1924         14" D.Fir, now root hole near record "S.36°E., 24.4 ft". 1924         20" now 29" dia., D.Fir with a fully healed double blaze, bears N.10°E., 34.4'. (Agrees w/rec.)         12" now 25" dia., D.Fir with a fully healed double blaze, bears S.71°E., 28.7'. Agrees w/rec. New BTs- 13" dia., Alder, single blazed and scribed "X CS BT" bears N.73½°W., 9.3'.         15" dia., G.Fir, double blazed and scribed "¼ S6 CS BT" bears N.32½°E., 8.0'.</p>