

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 100671

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 6, T28-7½

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Under Contract #109 dated 1924
(DCSO records, Volume 14 Page 5853)

Intersect W. bdy. of original Section 6.
At this point, Set an Iron post, 3 ft. long, 3" dia., 26" in
the ground, for NE. cor. of T. 28 S., R 7½ W., with brass cap
marked:

S 6 |
T28S |
R7½W |
1924

from which

A Fir 24" dia., bears S.24½°W., 46 lks. dist., marked
T28S R7½W S6 BT.

A Fir 12" dia., bears S.65½°W., 31 lks. dist., marked
T28S R7½W., S6 BT.

Ford's original standard cor. of T.28S., Rs. 7 and 8 W. re-
established as NW. cor. of T.28S R7W., bears N.0°41'E., 8.78
chs. (See DCSO records, Vol. 12 Page 5222)

H.L. Eppstein, Co. Surveyor - June 30, 1930 - M 1-73
C.S. Files 14/44 and 14/59; Vol. 4 Page 11

Standard government pipe.

Witness Trees:

24" Red Fir S.23°W., 30.0 ft.
12" Red Fir S.63°W., 20.0 ft.