

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 120140

PRIMARY CORNER DESCRIPTION Center West 1/16 Sec 31

Alias 915010 Description AP 1 Tract 62
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Mensch, 1924, (DCSO records, Vol. 14 Pg 5907)

Point for W center 1/16 sec. cor. of orig. sec. 31.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for
Cor. No. 1 of this survey, with brass cap mkd:
 C W 1/16 S31 C
 AP1 |
 TR62 |
 1924
No BTs or other objects available, no stones available for mound.

Arthur Boyer - Oct. 1962 - M 24-31

Fd. USGL0 brass monument "W 1/16 Cor. Sec. 31 Tr. 52"

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 4/4/2001 - C.S. File 66/21-8

Found - 1924 GL0 brass cap/iron pipe protrudes 18" out of
ground badly bent southwest, mkd:
 S31
 AP 1 | W 1/16
 TR 62 |
 1924
New - 17" dia., I.Cedar double blazed & scribed "CW 1/16 S31
CS BT" bears S.25°W., 39.3 ft.
1/2" I.D. iron pipe flush with ground bears N.72°W., 32.1
ft. (M 24-31)
5/8" I.R. LS2339 flush w/ground bears N.25¼°W., 60.1 ft
5/8" I.R. LS2339 flush w/ground bears N.2½°W., 48.5 ft
5/8" I.R. LS2339 flush w/ground bears N.41½°E., 81.1 ft
GL0 BC/IP straightened measures 36" long, set at plumb
position, protrudes 4" above ground.
Compass decl. 17 3/4°E.

Douglas Co. Surveyor's Office - Crew: Jeff Lorsung -
7/30/2025 - C.S. File 67/61-5

Found - GL0 brass cap (properly mkd)
5/8" iron rod with red cap N.72°W., 32.1 ft., flush
with ground.
5/8" iron rod N.25¼°W. 60.1' flush w/ground LS 2339
5/8" iron rod N.2½°W., 48.5 ft flush w/ground LS 2339
5/8" iron rod N41½°E., 81.1 ft per record.
Witness sign on angle iron 1 ft. east.
OCRS COORDINATE SYSTEM COTTAGE GROVE-CANYONVILLE ZONE
43°05'40.17965 N 123°34'33550 W Compass decl. 14¼°E.