

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs 19 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5776)

Set quar. sec. post at average dist., from which
A B.Oak 10" dia., bears S.33°W., 125 lks. dist.
A B.Oak 12" dia., bears N.27°W., 148 lks. dist.

GLO resurvey by Mensch, 1924 (DCSO records, Vol. 14 Page 5888)

Apportioned Distance.
Set an Iron post, 3 ft. long, 1 in. dia., 28 ins. in the ground, with brass cap marked: $\frac{1}{4} \frac{S 19}{S 30}$
1924
from which
A Fir 18" dia., bears S.60°W., 9 lks. dist., mkd. $\frac{1}{4}$ S30 BT.
A W.Oak 8" dia., bears N.42 $\frac{1}{4}$ °W., 26 lks. mkd. $\frac{1}{4}$ S19 BT.

Doug. County Surveyors Office - James W. Byron, Deputy - Clete Putnam; Milo Godfrey - May 1961 - C.S. File 52/79-10

Found - Both BTs OK. I open NW BT and find good scribing. SW BT bears S.48°W., 9.6 ft. Record, S.60°W., 6.0 ft.
We do not find brass cap.
Set Brass cap under E-W fence, mkd: County Surveyor $\frac{1}{4} \frac{S 19}{S 30}$
Office, 1961 T28S R7W
New BTs -7" W.Oak bears N.2°W., 18.7 ft. scribed $\frac{1}{4}$ S19 CSBT
18" R.Fir bears N.55°E., 15.6 ft. scribed $\frac{1}{4}$ S19 CSBT

Donald Bentz, L.S. #839 - For: Bob Carrico, April 1989 - M 107-76

Found - 36" D.Fir bears S.48°W., 9.6 ft. with scar.
30" D.Fir bears N.55°E., 15.6 ft. with scar.
(Did not find brass cap of record)
Set - 5/8" x 30" Iron rod with cap marked "Bentz Surv. Inc."

Doug. County Surveyors Office - Randall Smith; Stephen Flause August 2, 1989 - C.S. File 64/1-9

Found - 8" now 10" dia. W.Oak. We open single blaze and find partial scribing "S", bears N.42 $\frac{1}{4}$ °W., 17.2 ft. (agrees w/rec) 1924 BT.

(Cont. Next Page)

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found - 18" now 36" dia. D.Fir with a fully healed single blaze bears S.48°W., 8.6 ft. (Rec. S.48°W., 9.6 ft. fits with nail found in center of trunk set above ground. 1924 BT.

7" now 7" dia. 18 ft. high, dead Oak snag, with a partially healed double blaze, scribing visible "¼ S19 CS BT" bears N.2°W., 18.7 ft. Agrees with record, 1961 Byron BT.

18" now 21" dia. D.Fir with newly axed off bark on face, burly wood seen, scribing probably not axed out, bears N.55°E., 15.6 ft. Agrees w/rec. 1961 Byron BT.

Set a 2 3/8" dia. brass cap on a 1 3/8" O.D. x 32" long I.P. protrudes 15" above ground. BC/IP is surrounded by a 2½ ft. dia. mound of stone. Cap marked: Douglas County Surveyors
T28S R7W S 30 S19 ¼ 1989

Fd. OK - Kristian DeGroot - Aug. 1995 - 1996-0004 A&B