

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 and 19

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5778)

Set quar sec. post at proper dist., from which
A R.Fir 20" dia., bears N.59°E., 34 lks. dist.
A R.Fir 5" dia., bears S.35°W., 42 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - April 1961 - C.S. File 49/50-51

Found - Orig. 20" now 34" W.Fir N.59°E., 22.4 ft. previously opened, shows good scribe "B".
Orig. 5" now 14" Fir, down and center rotted, S.35°W., 27.7 ft. (record) We find should be S.35°W.

Set Brass cap at cor. mkd. County Surveyors Office 1961 $\frac{1}{4}$ S18
T28S R7W S19

New BTs -15" W.Fir bears S.44°W., 5.0 ft. scribed $\frac{1}{4}$ S19 CS BT
10" W.Fir bears N.32°W., 17.0 ft. scribed $\frac{1}{4}$ S18 CSBT

BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20040-1)

From the 1/4 sec. cor. of secs. 18 and 19, perpetuated by Byron, Deputy County Surveyor, in 1961, from original evidence no longer in existence,, monumented with an iron post, 1½" diam., firmly set, projecting 15" above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T28S R7W

S18

1/4 _____

S19

1961

from which bearing trees mkd. by Byron
A fir, 18" diam., bears S.36 3/4°W., 8½ lks., with healed double blaze.

A fir, 17" diam., bears N.32°W., 25½ lks., with healed double blaze.

From this point, U.S. Coast and Geodetic Survey triangulation station 'TENMILE,' bears S.56°21'17"E., 42.216 chs. (mean bearing and sea level distance); monumented with a brass cap cemented flush in solid rock, with top mkd. TENMILE 1942-1976.