

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 7 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5779)

Set quar. sec. post at proper dist., from which
A W.Oak 22" dia., bears S.56°E., 50 lks. dist.
A B.Oak 18" dia., bears N.25°E., 18 lks. dist.

Arthur Boyer, March 8, 1957 - C.S. M 4-74

This corner was lost or obliterated. Re-establish corner by proportional measurement.
Set an 3/4" Iron post for corner point.
From which:
18" Fir bears N.35°W., 17.5 ft. mkd. ¼ S 7 1581 BT.
20" Fir, stump, S.6°W., 30 ft. mkd. ¼ S 18 BT.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - May 1961 - C.S. File 49/50-58

Found - Both BTs as recorded by Boyer. NW BT down.
We do not find Iron pipe at corner.
Set Brass cap at cor. mkd: County Surveyor's ¼ S 7 T28S
Office, 1961 518 R7W
New BTs -12" Cedar bears N.59°E., 30.0 ft. scribed ¼ S7 CSBT
10" W.Fir bears S.51°W., 28.3 ft. scribed ¼S18 CSBT

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20018)