

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 and 7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Pages 5780-81)

-----  
Set quar. sec. post at proper dist., from which  
A Laurel 4" dia., bears N.28°E., 12 lks. dist.  
A Laurel 14" dia., bears S.5°W., 16 lks. dist.

Arthur Boyer, #1581 - W. Monger; W. Lockwood; H. Eppstein  
Nov. 17, 1958 - M 13-19

-----  
Set Stake.  
21" Fir S.6°30'W., 35 ft. scribed ¼ S7, 1581 BT.  
21" Fir N.34°W., 39 ft. scribed ¼ S6 1581 BT.  
Corner 50 ft. West of creek. Creek, N & S.; 700 ft. South of  
mouth of Creek on NE slope by uproot.

Arthur Boyer, Wit: Northcraft - For: W. V. Monger - Aug. 1965  
C.S. File 51/317

-----  
Found - All old bearing trees down.  
1" Pipe, previously set. Added steel fence post.  
New BTs -24" Fir N.19°30'W., 33.5 ft. mkd. ¼ S6 1581 BT.  
9" Fir S.74°E., 18.4 ft. mkd. ¼ S7 1581 BT.

Doug. County Surveyors Office - Victor Cangie; James Cook -  
April 1, 1976 - C.S. File 59/8-13

-----  
Found - 24" now 25" Fir that bears N.19½°W., 33.5 ft., alive  
and well - good scar.  
9" now 11" Fir that bears S.74°E., 18.4 ft.,  
healthy, shows good double blaze; grown over.  
1" x 24" Iron pipe at corner point.  
Steel fence post set by Boyer in 1965.

Set 1" x 30" I.P. with brass cap at cor. mkd: County Surveyor  
T28S R7W  
S6  
S7  
1976

Set line crossing tag East side of BLM road #28-8-12.  
Compass declination setting: 20° East.

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, &  
Robert J. Chappel, Cadastral Surveyor, under Group #1585,  
surveyed May 1991/May 1994 - (DCSO rec Vol. 52 Pages 20023-4)

Fd. Ok by Troy Rambo, 2/2010 - M160-41