

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Arthur Boyer, #1581 - W. Monger; W. Lockwood; H. Eppstein -
Nov. 17, 1958 - M 13-19

Set Stake

14" W.Fir N.75°30'W., 64 ft. scribed Cen. S6 1581 BT.

18" W.Fir N.38°E., 35 ft. scribed Cen. S6, 1581 BT.

On steep side hill slope 300 ft. South of a creek.

Doug. County Surveyors Office - Gary L. Langlitz, Deputy -
Greg E. Quibell; Danna L. Ingram - Oct. 1, 1975 - C.S. File
57/36-13

Found - 14" now 20" W.Fir, alive & in good condition, mkd.
by Boyer, 1958, bears N.75½°W., 64.0 ft. with
scribe marks "6" visible on partially healed
blaze.

18" W.Fir, alive, also mkd. by Boyer, bears N.42°E.,
35 ft. (Rec. N.38°E., 35.0 ft.) with scribing
"Cen S6 1/16" and other illegible markings on an
unhealed blaze. (Note: record markings are "Cen
S6 1581 BT")

We also find unrecorded 1" I.P. bearing N.69½°W.,
4.8 ft. from the true corner point.

At the true corner point determined by the above shown
measurements, we set 1" x 30" I.P. with brass cap attached

mkd: DOUGLAS CO. SURVEYOR T 28 S Sec.6
1975 C 1/4 o
R.7.W

Compass declination setting: 20° East.

Victor McLind, surveyed for David Monger, Dec. 1996 thru
Feb. 1998 - M 128-40

Found - 1" pipe with 2½" Co. Surveyor's brass cap
16" Fir stump, open worn face, no scribes visible,
bears N.42°E., 35.4 ft.

22" Fir, healed double blaze, bears N.75½°W.,
64.0 ft.

New BT- 8" Fir, blazed and scribed "C¼ S6 BT"
bears S.14°W., 13.7 ft.

Fd. Ok by Troy Rambo, 2/2010 - M160-41