

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION North ¼ cor. Sec. 6 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Fred Mensch, Deputy under Contract #109 dated 1924 (DCSO records, Volume 14 Page 5877)

Apportioned distance.
Set an Iron post, 3 ft. long, 1" dia., 18" in the ground in mound of stone, for standard ¼ sec. cor. of sec. 6, with brass cap marked:

SC ¼ S6
1924

from which

A W.Oak 10" dia., bears S.47°E., 4 lks. dist. marked
S C ¼ S6 BT.

A W.Oak 16" dia., bears S.85°W., 23 lks. dist., mkd.
S C ¼ S6 BT.

(Ford's 1/4 Cor., see Vol. 14 Page 5222)

The cor. established by Hathorn for the standard ¼ sec. cor. of sec. 6, restored as angle point, bears S.34°33'W., 8.97 chs. (See DCSO records, Vol 12 Page 5231)

H.L. Eppstein, Co. Surveyor - Witn: B.A. Lane; Fitzpatrick Hollis Green - June 1930 - M 1-73; C.S. 14/59; & "old" renewal book Pg. 111

Standard govt. post ¼ S6 set by Mensch in 1924. Witness trees as follows:

W.Oak 12" dia. bears S.87°45'W., 15.0 ft.

W.Oak 10" dia., bears S.48°30'E., 28.7 ft.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnman - Feb. 1961 - C.S. File 49/79-33

Found - Brass cap out of ground. Reset from now 24" W.Oak S.85°W., 15.0 ft., shows good scribe.

New BT - 8" R.Fir bears S.18°E., 45.0 ft. scribed N ¼ S6 CS BT.

Doug. Co. Surveyors Office - Randall W. Smith; Stephen Flause Sept. 13, 1984 - C.S. File 62/21-30

Found - 1924 GL0 brass cap on a 2" I.P. protrudes 16" above ground, properly marked.

16" now 27" W.Oak with a well healed single blaze bears S.87°W., 15.8 ft. (Rec. S.85°W.,

15.0 ft.) 1924 BLM resurvey.

(Cont. Next Page)

