

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5773)

Set quar. sec. post, from which
A W.Oak 6" dia., bears N.5°E., 270 lks.
A W.Oak 10" dia., bears S.18½°W., 200 lks.

(See Cole's notes of 1913 in Field Book 33 Pg. 11 for his possible ¼ cor. BT discrepancy) vl

G.G. Stewart, D.C.S. - Wit: Harold Nichols; S. McBee; W.H. Goats - Nov. 1922 - Vol. 3 Pg. 129; C.S. File 5/28; M 3-74

Set Iron pipe from one O.B.T. Set N.18°E., 132.0 ft. from tree. Gov't notes call for tree bearing S.18½°W., 132.0 ft.
Marked:
W.Oak 12" dia., bears S.75½°W., 36.2 ft.
W.Oak 14" dia., bears S.18°W., 132.0 ft. (O.B.T.)

GLO resurvey by Mensch, 1924 (DCSO records, Vol. 14 Page 5883)

Intersect the point for ¼ sec. cor., located by record bearing and distance from the orig. SW. bearing tree, on which the marks are plain. The NE bearing tree was not found. At the exact cor. point
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd: ¼
S31*S32
1924

from which
Orig. BT, a W.Oak 26" dia., bears S.18°W., 200 lks.
A W.Oak 16" dia., bears S.66°W., 48 lks. dist. mkd. ¼ S31
BT. (New BT)
No trees in sec. 32.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 2/22/2001 - C.S. File 66/19-42

Found - 1924 GLO brass cap iron pipe protruding 12" above ground 2 ft. West of a N-S fence line.
10" now 49" dia., W.Oak w/fully healed blaze, bears S.18°W., 132.0 ft. (Rescribed "¼ S31 CS BT") OBT
16" now 18" dia., 1½ ft. high Oak stump with a rotted blaze, bears S.66°w., 31.7 ft. 1924

continued next page

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Unrecorded triple trunked Ash fd., with a partially healed double blaze, illegible scribing visible on 18" dia., southerly trunk. Center of scribed trunk bears N.13°E., 9.6 ft.

New - 16" dia., W.Oak double blazed & scribed "¼ S32 CS BT" bears S.45 3/4°E., 261.2 ft.

17" dia., I.Cedar double blazed & scribed "¼ S31 CS BT" bears S.62°W., 69.0 ft.

See last Pg for pictures.

FD. BC G. Lang 10/10, M161-28

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

