

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5775)

Set a post, cor. of secs. 19, 20, 29 and 30, from which
A B.Oak 15" dia., bears S.26°W., 27 lks.
A W.oak 12" dia., bears S.26°E., 110 lks.
A Pine 30" dia., bears N.67°E., 23 lks.
A B.Oak 25" dia., bears N.23°W., 29 lks.

GL0 resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pg. 5887)

Intersect the point for cor. located by measurement from the original bearing trees, on which the blazes are plain and some marks visible. The SE BT could not be found.

At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd:

T28S	R7W
S19	S20
S30	S29
1924	

from which, (original bearing trees)

A Pine 36" dia., bears N.67°E., 23 lks. dist., now dead and fallen.

A B.Oak 16" dia., bears S.26°W., 27 lks. dist.

A B.Oak 30" dia., bears N.23°W., 29 lks. dist., re-marked T18S R7W S19 BT.

New Bearing trees:

A Fir 20" dia., bears N.1°E., 46 lks. dist., mkd. T28S R7W S20 BT.

A Fir 8" dia., bears S.15°E., 13 lks. dist., mkd. T28S R7W S29 BT.

A Fir 16" dia., bears S.78°W., 11 lks. dist., mkd. T28S R7W S30 BT.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - May 1961 - C.S. File 49/50-55

Found - Brass cap at corner and all Mensch BTs. All show good scars and are in good condition.

New BT - 18" R.Fir bears N.72°W., 11.3 ft. scribed S19 T28S R7W CS BT.

Fd. OK - Kristian DeGroot - Aug. 1995 - 1996-0004 A&B

Fd. Ok by G.Lang, 4/2008 - M158-39