

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 19 and 20

| | | | |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5776-77)

Set quar. sec. post, from which
A W.Oak 10" dia., bears N.50°E., 75 lks. dist.
A B.Oak 12" dia., bears S.80°W., 54 lks. dist.

Wm. C. Stiles, Seek Inc. For: L & H Lumber Co. - March 23, 1967 - C.S. File 55/32; M 32-76

Established by single proportionate measurement.
S.0°13'03"E., 2440.10 ft. from cor. to secs. 17, 18, 19, 20.
At the point for the cor., a nail was set and an "X" chiseled in rock, from which
18" Cedar scribed ¼ S19 BT bears S.77°04'02"W., 75.5 ft.
14" Cedar scribed ¼ S20 BT bears N.84°23'42"E., 83.3 ft.

Greg Lang - For: Elizabeth Brien - April 2008 - M158-39

Reported as not found.
"I did not find the corner nail or trees previously done by Stiles (M32-76)"