

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5777)

-----  
Set a post, cor. of secs. 17, 18, 19 and 20, from which  
A Laurel 8" dia., bears S.10°W., 38 lks. dist.  
A Maple 12" dia., bears N.45°W., 76 lks. dist.  
A R.Fir 40" dia., bears N.23°E., 16 lks. dist.  
A R.Fir 20" dia., bears S.73°E., 120 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - Oct. 12, 1959 - C.S. File 49/50-30

-----  
Found - Orig. 20" now 40" Fir, S.73°E., 79.2 ft. shows part of good bark scribing.  
Orig. 40" now down 50" R.Fir, N.23°E., 10.6 ft. Old axe marks found, no scribing.  
Orig. SW & NW BTs no found.

Set Brass cap at cor. mkd: County Surveyor's Office, 1959

S 18 | S 17  
S 19 | S 20 T28S R7W

New BTs -6" Cedar bears N.56°W., 15.8 ft. scribed S18 CS BT.  
14" Maple bears S.26°W., 19.2 ft. scribed S19 T28S R7W CS BT.  
10" Maple bears S.29½°E., 30.8 ft. scribed T28S R7W S20 CS BT.  
5" Cedar bears N.43°E., 42.6 ft. scribed S17 CS BT.  
Ravine is approx. 50 ft. East of corner.

Doug. County Surveyors Office - Larry Monrean, Deputy - J.M. Powell - Oct.7, 1983 - C.S. File 62/9-17

-----  
Found - 1959 DCSO brass cap, properly mkd., on 1" Iron pipe, bent over to the east, nearly out of ground.  
Orig. 20" now 32" Fir with faint bark scribing, bears S.73°E., 79.2 ft. This tree is across ravine from corner.

14" now 15" double trunk Maple bears S.26°W., 18.7 ft. (Rec. 19.2 ft. checks center of blazed trunk) Has well healed blaze.

10" now 12" Maple bears S.29½°E., 30.8 ft. Tree has well healed blaze.

5" now 8" Cedar bears N.43°E., 41.1 ft. (Rec. 42.6 ft.) Has a well healed blaze.

NW Cedar BT is down.

Set - Reset monument at corner position.

continued next page

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BT - 6" I.Cedar double blazed & scribed "S18 CSBT" bears  
N.10°W., 44.9 ft.  
Cor. lies on steep es'ly slope about 50' W. of ravine bottom.

Fd. Ok by G. Lang, 4/2008 - M158-39