

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5778)

Set quar. sec. post, from which
A R.Fir 30" dia., bears S.50°E., 45 lks.
A R.Fir 24" dia., bears N.35°W., 13 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - April 1961 - C.S. File 49/50-53 (See also C.S. 49/50-31 for 1959 search)

Found - 40" Fir S.50°E., 29.7 ft., measured on slope, with characteristic Ford scribing "¼ 2 B1" bark scribe.
32" Fir S.32°W., 3.0 ft. with old scribing "BV" (bark scribe)
40" Fir stump, cut low, bears N.85°W., 8 ft.
Old scribing on 2 trees found, both face corner as set. Both trees have been rescribed since orig. scribing.

Set Brass cap at cor. mkd: County Surveyor's Office, 1961
S 18 | S 17 ¼ T28S R7W
SE BT is S.50°E., 28.0 ft. (horizontal measure)
A scribed stake, approx. 10 to 15 yrs. old, 4" sq. and 18" above ground, bears N.32°E., 7 ft.

BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20015-6)

From the 1/4 sec. cor. of secs. 17 and 18, perpetuated by Byron, Deputy County Surveyor, in 1961,; monumented with an iron post, 1½" diam., firmly set, projecting 12" above ground, with brass cap mkd. DOUGLAS COUNTY SURVEYORS OFFICE
T28S R7W
¼ S18 | S17
1961

from which a remaining original bearing tree
A fir, 40" diam., bears S.50°E., 41 lks., with scribe marks ¼ BT visible on a bark blaze. (Record, 45 lks.)
and the remains of bearing trees mkd. by person(s) unknown
A fir, 32" diam., bears S.24¼°W., 4½ lks., with fragmentary scribe marks visible on a bark blaze.
A sawed fir stump, 40" diam., bears N.84°W., 11 lks., no marks visible.

Fd. Ok by G. Lang, 4/2008 - M158-39