

PRIMARY CORNER DESCRIPTION Sec Cor 5, 6, 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5780)  
-----  
Set a post, cor. of secs. 5, 6, 7 and 8, from which  
A Dogwood 6" dia., bears N.45°E., 12 lks. dist.  
A R.Fir 20" dia., bears N.33°W., 16 lks. dist.  
A R.Fir 18" dia., bears S.5°E., 12 lks. dist.  
A R.Fir 30" dia., bears S.78°W., 14 lks. dist.

GL0 resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pg. 5894)  
-----  
Intersect the point for cor., located from the original bearing trees. Marks are legible on the bark of the old Firs. The Dogwood has rotted out. At the exact cor. point Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd:   T28S R7W  
  S6|S5  
  S7|S8  
from which original bearing trees:  
A Dogwood 12" dia., bears N.4°E., 12 lks. (not N.45°E)  
A Fir 48" dia., bears S.87°E., 14 lks. (Not S.5°E. 12 lks.)  
A Fir 40" dia., bears S.38°W., 14 lks. (Not S.78°W.)  
A Fir 40" dia., bears N.60°W., 19 lks. (Not N.33°W, 16 lks.)  
New Bearing trees:  
A Fir 12" dia., N.47°E., 24 lks. mkd. T28S R7W S5 BT.  
A Maple 9" dia., S.42°E., 102 lks. mkd. T28S R7W S8 BT.  
A Fir 10" dia., S.77°W., 69 lks. mkd. T28S R7W S7 BT.  
A Fir 16" dia., N.82°W., 30 lks. mkd. T28S R7W S6 BT.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - March 1961 - C.S. File 49/50-39  
-----  
Found - Brass cap at corner and stumps of two 1924 BTs showing scribing.  
New BTs -14" Yewwood bears N.12½°E., 29.5 ft. scribed S5 T28S R7W CS BT.  
Chiseled 2 in. + (cross) and drove PK nail at center bears N.50°E., 28.3 ft. in sandstone outcrop on steep West slope exposed rock about 7 ft. high and 10 ft. across.  
No other trees near.

Doug. County Surveyors Office - A. Victor Cangie; Jim H. Cook April 27, 1976 - C.S. File 59/8-24  
-----  
(Cont. Next Page)

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. 5, 6, 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found - 2" 1924 GLO B.C, properly stamped, in good condition but bent toward South. We straighten and secure in ground.  
12" Fir stump, bears N.47°E., 15.8 ft. scribed "R7W S5 BT" visible. This is a 1924 BT.  
14" now 16" Yewood bears N.12½°E., 29.5 ft. scribing visible on partly healed blaze.  
A PK nail embedded in a sandstone outcrop bears N.50°E., 28.3 ft. We found no other evidence.  
New BTs -9" D.Fir bears due South, 33.4 ft. mkd. "T28S R7W X (4"x4") CS BT" in a double blaze.  
6" D.Fir bears S.48°W., 70.6 ft. mkd. "T28S R7W S7 CS BT" in a double blaze.

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCS0 records Vol. 52 Page(s) 20022)