

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 and 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5781)

-----  
Set quar. sec. post at proper dist., from which  
A Fir 8" dia., bears N.10°E., 24 lks. dist.  
A Fir 30" dia., bears S.53½°W., 55 lks. dist.

GLO resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pg. 5896)

-----  
Apportioned Distance.  
Set an Iron post, 3 ft. long, 1" dia., 28" in the ground,  
with brass cap marked:           ¼  
  S6 S5  
  1924

from which  
A Laurel 22" dia., bears S.83°E., 17 lks. dist. marked ¼  
S5 BT.  
A Laurel 26" dia., bears S.44°W., 31 lks. dist., marked ¼  
S6 BT.

Fd. Brass cap, A. Boyer, Oct. 1958, M 13-19

Fd. OK by McLind, surveyed Dec. '96 thru Feb. '98 - M 128-40