

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 200674

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 5 only

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

1924 GLO resurvey by Mensch, (DCSO records, Vol. 14 Page 5850)

Intersect original line bet. secs. 5 and 6.
At this point, Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for NW. cor. sec. 5 only, with brass cap marked:

| S5
| T28S
| R7W
1924

from which

A Fir 20" dia., bears S.41°E., 50 lks. dist. marked T28S R7W S5 BT.

A Fir 7" dia., bears S.9°E., 37 lks. dist., marked T28S R7W S5 BT.

Ford's original standard cor. of secs. 5 and 6, reestablished as NE cor. of sec. 6 only, bears N.4°22'W., 5.82 chs. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - Feb./March 1961 - C.S. File 49/79

Found - Brass cap at corner and both BTs. SE BT now snag only, shows good scribing "W S5 BT", now 30", S.41°E., 33.0 ft.

New BT - 24" W.Fir bears S.49°E., 45.0 ft. scribed NW S5 CS BT.

Doug. County Surveyors Office - L.E. Monrean, Deputy - Pete Earle; A. Cangie - July 8, 1976 - C.S. File 59/18-3

Found - 1924 GLO brass cap, properly marked.
20" now 18" rotted snag, bears S.41°E., 33.0 ft. Snag scribed "W S5 BT".

7" now 18" Fir bears S.9°E., 24.3 ft. Tree has well healed blaze.

24" now 26" W.Fir now a windfall bears S.49°E., 45.0 ft. Tree has well healed blaze.

New BT - 23" D.Fir bears S.83½°E., 55.6 ft. Tree double blazed and scribed "T 28 S R 7 W S 5 CS BT"

Fd. OK by McLind, surveyed Dec. '96 thru Feb. '98 - M 128-40