

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 20 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5776)

-----  
Set quar. sec. post at average dist., from which  
A B.Oak 20" dia., bears S.89°W., 135 lks. dist.  
A B.Oak 18" dia., bears N.68°E., 180 lks. dist.

Doug. County Surveyors Office - G.G. Stewart, Deputy - Wit: C. Crocker; J.H. Porter - For: Bogard Real Estate - Sept. 1922 - Vol. 3 Pg. 126; C.S. Files 3/40 and 5/22

-----  
Reset from two O.B.T.s agree with distance but bearing of one is 90° off. Marked:  
Fir 6" dia., FOR CORNER.  
Laurel 12" dia., bears N.76°W., 37.6 ft.  
B.Oak 8" dia., bears S.20½°E., 23.6 ft.

Doug. County Surveyors Office - James Byron, Deputy - April 1956 - C.S. File 47/176; RM 1-15

-----  
Found - 18" (now) Fir at corner showing old blazes.  
8" B.Oak now 12", with face rotted and no scribing visible - checks for bearing and dist. to corner, S.20½°E., 23.0 ft.  
The 12" Laurel, N.76°W., 37.6 ft. NOT FOUND.  
I also find 18" B.Oak with open face that shows faint scribe marks - may be orig., and bears N.68°E., 118.8 ft.  
Set an Iron pipe with brass cap at West face of 18" Fir corner tree, mkd. "¼ S29, T28S R7W, County Surveyor's Office, 1956", from which  
10" R. Fir bears S.9½°W., 9.4 ft. scribed ¼ S29 CS BT.  
10" R.Fir bears N.25°W., 38.4 ft. scribed ¼ S20 CS BT.

Fd. OK - K. DeGroot - March 1996 - M 123-42  
FD. OK - D. Edwards - Sept. 1996 - 1996-0090  
Fd. Ok by G. Lang, 4/2008 - M158-39 (BC bears N.57°W. 2.0')

Fd. corner tree, BC bears N.56°15'W., 2.2' D. Edwards 11/2023 M183-10