

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 240340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Wm. C. Stiles, Seek, Inc. For: L & H Lumber Co. - March 23, 1967 - C.S. File 55/32; M 32-76

-----  
Point for cor. is midway btwn. N & S ¼ corners and E & W ¼ corners.

A Nail was driven in a rock face, from which  
12" Cedar scribed C ¼ S20 BT bears N.49°06'03"E., 74.98'.  
6" Oak scribed C ¼ S20 BT bears S.28°48'38"W., 8.95 ft.  
12" Oak scribed C ¼ S20 BT bears S.39°47'17"E., 76.59 ft.  
An "X" chiseled in a rock face bears N.56°44'47"W., 30.4 ft.

All bearings were established through solar observation.

Doug. County Surveyors Office - John M. Powell, Deputy - Jan. 10, 1972 - C.S. File 54/113-22

-----  
CORNER REPORT ONLY

Found at C. ¼ cor., nail in center of 4" + 5" under ground.  
Found - 12" Cedar, N.49°E., 75.0 ft. scribe visible.  
12" W.Oak S.42°E., (Rec. S.39°E., 76.6 ft. scribe visible.  
6" W.Oak S.25°W., (Rec. S.28°W.) 8.9 ft. scribe visible.  
+ on 5.0 rock face, N.56°W., 30.4 ft., Add this dist. to record.

Greg Lang - For: Elizabeth Brien - 4/2008 - M158-39

-----  
Set - 5/8" (x 30") iron rod (with plastic cap marked "LANG SURVEYING") protruding 14" above ground, 8" after piling stones around it, at the center ¼ corner of section 20.

14" double oak, same as used by Stiles, bears S.31¾°E., 60.60'

10" W.Oak, same as used by Stiles, bars S.86½°W. 21.60'

Concrete nail in "X" on 6' boulder, same as used by Stiles, bears N.62¼°W., 47.60'

25" D.Fir bears N.75¾°E., 76.90' scribed "C¼ S20 BT"