

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5777)

Set quar. sec. post at average dist., from which
A Maple 3" dia., bears S.80°W., 45 lks. dist.
A Fir 10" dia., bears N.30°W., 91 lks. dist.

Wm. C. Stiles, Seek, Inc. For: L & H Lumber Co. - March 23, 1967 - C.S. File 55/32; M 32-76

Established by single prop. measurement, S.89°30'31"W., 2599.04 ft. from sec. cor. 16, 17, 20 and 21.
Set - 1½" galv. iron pipe, from which
A Nail in a rock face bears N.39°37'26"E., 16.20 ft.
A chiseled "X" in a large stone bears S.38°28'26"W., 36.60 ft.

Doug. County Surveyors Office - John Powell, Deputy - Heritage and Schulze - Jan. 10, 1972 - C.S. File 54/113-21

Found - Nail in part of +, 0.5 ft below ground in solid rock + in stone, S.35°W., (Rec. S.38½°W) 36.6 ft.
Nail in rock, N.43°E., (Rec. N.39½°E) 16.2 ft.
Note: Record bearings based on Solar.
Renewals - Old Bearing Object:
5" + on rock point which protrudes 1.0 ft. above ground, S.35°W., 36.6 ft. 5" + faces about East.
New Bearing Object:
10" + bears N.3½°W., 23.2 ft. (Note: This + is on 6.0 ft. vertical rock face about 2.0 ft. from base and facing about East.
Corner lies in large rocky opening on East slope.

Greg Lang - For: Elizabeth Brien - 4/2008 - M158-39

Set - 5/8" (x 30") iron rod (with plastic cap marked "LANG SURVEYING") at the ¼ corner common to sections 17 & 20.
7/8" steel spike (4' up in vertical rock face) bears S.27°51'E., 48.55'
7/8" steel spike in large vertical rock face bears S.42°22'W., 87.16'
Existing pk nail 2' up in vertical rock face bears N.0°03'W., 14.92'
7/8" steel spike in a rock point bears N.71°34'E 12.80'