TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 8 and 17

Alias Description
Alias Description
Alias Description
Alias Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5779)

Set quar. sec. post at average dist., from which
A B.Oak 18" dia., bears S.50°E., 79 lks.
A Laurel 30" dia., bears S.8°W., 17 lks.

Virgil Broadwater, For: W.B. Smith - Feb. 18, 1972 - M 44-46

Set 1½" I.P. 30" in ground, 8" above ground.
BTs - 12" D.Fir bears S.48°21'E., 21.0 ft. "¼ S17 T28S R7W BT"
12" D.Fir bears N.70°09'W., 26.4 ft. "¼ S8 T28S R7W BT"

BLM resurvey by Bishop and Rogers, under Group #1124 - Survey, April 1983/Jan. 1984 (DCSO records, Vol. 46 Page 17755-56)

The ¼ sec. cor., reestablished by Broadwater, 1972 monumented with an I.P. 1½" dia., firmly set, projecting 8" above ground There is no remaining evidence of the orig. corner. This position is accepted as the cor., from which bearing trees mkd. by Broadwater:
A Fir 14" dia., bears S.48½°E., 31 lks. dist., with fragmentary scribe marks visible on a partially healed double blaze.
A Fir 14" dia., bears N.70°W., 40 lks. dist., with a healed double blaze.
At the Corner point
Set an alum. post, 28" long, 2½" dia., 24" in the ground, with alum. cap mkd: T 28 S R 7 W

1/4 S 8 / S 17
1983

Deposit the iron pipe alongside the iron post.

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20017)

Fd. Ok by G. Lang, 4/2008 - M158-39