

TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 5 and 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5780)

-----  
Set quar sec. post at average dist., from which  
A Laurel 15" dia., bears N.45°E., 30 lks. dist.  
A Laurel 5" dia., bears S.8°E., 24 lks. dist.

GL0 resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pg. 5893)

-----  
Apportioned Distance.  
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd:  $\frac{1}{4} \frac{S 5}{S 8}$   
1924

from which  
A Laurel 18" dia., bears S.1½°W., 20 lks. dist. mkd. ¼ S8 BT.  
A Fir 8" dia., bears N.19°W., 41 lks. dist., mkd. ¼ S5 BT.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - March 1961 - C.S. File 49/50-40

-----  
Found - Brass cap at corner and shell of stump of SW BT and stub of NW BT, check record OK.  
New BTs -10" W.Fir bears S.51°W., 48.0 ft. scribed ¼ S8 CS BT  
15" Cedar bears N.24½°E., 71.2 ft scribed ¼ S5 CS BT

Found OK, DCSO, May 3, 1976, C.S. File 59/8-26