TOWNSHIP 28 RANGE 07 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION W.P. for 1/4 Cor. S. 5 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5221)

Set ¼ sec. post, from which
A B.Oak 7" dia., bears N.40°W., 40 lks. dist.
A B.Oak 8" dia., bears S.73°W., 39 lks. dist.

1924 GLO resurvey by Mensch (DCSO records, Vol. 14 Pages 5874-75)

Intersect the point for standard ¼ sec. cor. of secs. 5, established by Ford, located by measurement from the original bearing trees. Marks are plain on the NW tree. Marks on the SW tree are overgrown and blazes not opened.
At the exact cor. point
Set an Iron post, 3 ft. long 1" dia.,28" in the ground, for

witness point, with brass cap marked: WP
1924
from which
New bearing tree, a Laurel 8" dia., bear S.65°E., 17 lks. dist., marked W P BT.
Original bearing tree, a B.Oak 16" dia., bears S.74°W., (not S.73°W), 39 lks. dist., remarked W P BT.
Original bearing tree, a B.Oak 12" dia., bears N.38°W., (not N.40°W.,) 40 lks. dist.
New ¼ sec. cor. of sec. 5 only, on center meridianal subdivision line of sec. 5 and on S. bdy.of sec. 32, bears S.4°54'E., 4.41 chs. dist.
The ¼ sec. cor. of sec. 5, established by Hathorn as standard ¼ sec. cor., restored as angle point, bears S.35°15'W., 5.39 chs. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - Feb/March 1961 - C.S. File 49/79-38

Found - Brass cap at cor. & stump of orig. SW BT., shows good reverse scribing.
Stump of SE BT. Orig. NW BT, not found.
New BTs -11" Laurel N.7°E., 24.4 ft. scribed WP CS BT.
8" R.Fir bears S.68°W., 45.8 ft. scribed WP CS BT.