

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 20 and 21

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 14 Page 5770)

Set quar post, from which
 A Laurel 10" dia., bears S.30°E., 57 lks.
 A B.Oak 6" dia., bears N.68°W., 50 lks.


Wm. C. Stiles, Seek, Inc. For: L & H Lumber Co. - March 23, 1967 - C.S. File 55/32; M 32-76

Cor. established by single proportionate measurement.
 At the point, set a 1½" galv. Iron pipe, from which
 A 12" Madrone bears N.42°57'31"E. 19.32 ft. scribed ¼ S21 BT
 8" D.Fir bears S.40°29'21"W., 36.25 ft. scribed ¼ S20 BT.

Fd. OK per pending BLM 1992 Survey - Bruce Shaner - 6/30/97
-See C.S. 65/15-3 for BLM line notes

BLM dependent resurvey by Bryan S. Seibold, & Robert J. Chappel, Cadastral Surveyor, under Group #1585, surveyed May 1991/May 1994 - (DCSO records Vol. 52 Page(s) 20011-2)

Point for the ¼ sec. cor. of secs. 20 & 21, at proportionate distance, there is no remaining evidence of the orig. corner. Set a stainless steel post, 28" long, 2½" diam., 22" in the ground, with brass cap mkd. T28S R7W



from which
 A fir, 13" diam. bears S.71 3/4°E. 91 lks., mkd. ¼ S21 BT.
 A fir, 12" diam., bears N.39°W., 2½ lks., mkd. 1/4 S20 BT.
 Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, a point established as the ¼ sec. cor. of secs. 20 & 21 by Wm Stiles, in 1967, bears S.67°10'00"W., 0.206 chs; monumented with an iron pipe, 1½" dia. firmly set, projecting 4" above ground, from which BTs mkd. by Stiles:

- A madrone, 17" diam., bears N.43½°E., 29 lks., with scribe marks S21 ¼ BT visible on partially healed blaze.
- A fir, 13" diam., bears S.42½°W., 55 lks., with healed blaze.

This corner was rejected due to improper control and erroneous position and was not used in this survey.

Fd. Ok by G. Lang, 4/2008 - M158-39